

Louvre Collection

Specifications



Louvre Collection Specifications

 <p>Construction: Engineered High Density Ply Core Hardwood with Tongue and Groove</p>	 <p>Edge Profile: 1-2mm Micro Beveled Edges and Ends</p>
 <p>Species: French Oak</p>	 <p>Installation: Nail, Staple, Glue, Float; Above Grade, At Grade, Below Grade</p>
 <p>Dimensions: 5/8" (Nominal Overall Thickness) X 9.4" (width) X 86.6" (75% long boards)</p>	 <p>Surface Treatment: 3D, advanced brush for a more pronounced grain texture</p>
 <p>Thickness of Surface Layer: 4mm</p>	 <p>Gloss: 3-7 degree</p>
 <p>Cutting Method: Sawn</p>	 <p>Moisture Content: 6%–9%</p>
 <p>Grade: ABCDEF</p>	 <p>Color Variation: Water-based Coloring</p>

Finish:
UV/6 primer+2 finish, Sherwin-Williams+overmat

Assembling Gap: ≤0.20mm

Length Deviation: ±0.5mm

Width Deviation: ±0.15mm

Thickness Deviation: ±0.2mm

Reactive Stain: Smoke+Reactive Stain

Surface Abrasion Resistance: ≥300r, S-33 Sand paper

Film Hardness: ≥2H

Static Bending Strength: ≥30MPa

Moisture Content: 6%-9%



Packaging

Area per carton: 34.10 Sqft. per Carton

Weight per carton: 70.55 Lbs

Warranties: 50 year residential finish warranty, 5 year commercial warranty. Please visit www.californiaclassicsfloors.com for the most current warranty information.



Environmental

Certifications: Floor Score Certified

Carb II Compliant: Yes

Lacy Act Compliant: Yes